

**Characteristics:**

White printable and cuttable smooth material that can be easily contour cut. Ideal for the production of samples and low-run orders of multi-coloured transfers. A shiny brilliant finish will be achieved thanks to the glossy printable surface.

**Application Information:**

100% cotton, cotton blends, 100% polyester\*, polyester blends

\*Before you print on polyester please make proofs to see the colour fastness, because polyester colours can staining.

**Printable Information:**

Solvent and Eco Solvent inks

**Availability:**

50 cm width, 30 m length

**Washability:**

up to 40°C

Wash and iron garment inside out

**Processing Instructions:**

Do not mirror image and please pay attention that the paper faces down. Ensure that the correct printing parameters are used and adjusted accordingly. The imprinted material has to repose for at least 2 hours if the cutting line lies inside of the motive. Remove excess material and affix the application tape CAD-COLOR® Magic Mask® onto the material. In order to avoid bubbles between the motive and the carrier, we recommend to use a squeegee. Remove image from carrier, place on garment and heat apply as listed below:

**Printing Parameters:**

Always pre-heat garment before starting the heat application for 5-10 seconds in order to remove possible moisture and / or chemical residue.

Temperature: 150°C - 160°C

Time: 12 seconds

Pressure: medium

Remove Magic Mask®: warm

**Accessories:**

Teflon® cover sheet, Grip cover sheet, EZ Weeder™, CAD-COLOR® Magic Mask®